
 25			
tjm sistem Tim Sistem, Noma Pazova, Serbia		DoP No: 0015/16.12.25 EN 16510-1 / EN16510-2-1:2023 NB - 1015	
Residential space heating appliances fired by wood logs			
Model:		LEDERATA ECO	
Load bearing capacity:		0 kg	
Safety distance from combustible materials		mm	Bottom dB= 0 Floor in front dF = 300 Ceiling dC = >750 Rear dR = 300 Side dS = 350 Side radiation area dL = 150 Front dP = 700
Emissions at : nominal heat output / reduced heat output		nominal	reduced
CO (at 13% O ₂)	mg/m ³	806	NPD
Dust (at 13% O ₂)	mg/m ³	31	NPD
NOx (at 13% O ₂)	mg/m ³	89	NPD
OGC (at 13% O ₂)	mg/m ³	42	NPD
Data for installation on a chimney at: nominal heat output / reduced heat output		nominal	reduced
Flue gas outlet temperature	°C	256	NPD
Minimum flue draught	Pa	12	NPD
Flue gas mass flow	g/s	4,9	NPD
Data for installation on a chimney regarding fire safety	class	T400G	
Heat output and energy efficiency of the appliance at nominal heat output / reduced heat output		Nominal	Reduced
Space heat output at nominal / reduced heat output (room + water)	kW	6,3	NPD
Energy efficiency at nominal / reduced heat output.	%	85	NPD
Season efficiency	%	75	
EEL index / Energy class		113 / A +	
Power consumption at nominal heat output	kW	/	
Power consumption at reduced heat output	kW	/	
Power consumption in standby mode	kW	/	
Fuel consumption at nominal heat output	Kg / h	1,67	
Use only recommended fuels!			
Recommended fuel		Wood logs	
Type of appliance		TYPE B	
Max. water operating pressure	bar	/	
Suitability for installation to a shared flue system		yes	
Information about the appliance operation		Appliance for intermittent operation	
Fume exhaust	mm	Ø120	
Voltage	V	/	
Frequency	Hz	/	
Electrical connection		/	
Please read and follow the user operating instructions before starting!			
Serial number			