

DECLARATION OF PERFORMANCE
According to Regulation (EC) 305/2011

No: 0013/16.12.25

1.	Unique identification code of the product-type:	Residential space heating appliance fired by wood logs: TS-L GLASS		
2.	Intended use /es	Residential solid fuel burning appliances: Roomheaters		
3.	Name, registered trade name or registered trade mark and contact address of the manufacturer:	TIM SISTEM d.o.o. Street Prva industrijska. No.9, Industrial area Nova Pazova 22 330 Nova Pazova, Serbia, e-mail: office@timsistem.rs		
4.	Name and address of the authorised representative	-		
5.	System of assessment and verification of constancy of performance of the construction:	System 3		
6.	The notified test laboratory has performed the initial test according to system 3. Noti-fied body(ies)	Notified Body number : 1015		
		Test report number: 30-18067/T		
7.	Harmonized standard:	EN 16510-1:2022, EN 16510-2-1:2023		
8.	Essential characteristics:			
	Mechanical resistance and stability			
	Maximum load of a chimney the appliance max carry	Mchim	0	kg
	Fire safety			
	Reaction to fire	A1 (According to EN 13501-1)		
	Safety in case of fire			
	Minimum distances to combustible materials - bottom	dB	0	mm
	Minimum distances to combustible materials - floor in front	dF	400	mm
	Minimum distances to combustible materials - ceiling	dC	>750	mm
	Minimum distances to combustible materials - rear	dR	300	mm
	Minimum distances to combustible materials - side	dS	400	mm
	Minimum distances to combustible materials - side radiation area	dL	200	mm
	Minimum distances to combustible materials - front	dP	750	mm
	Hygiene, health and environment			
	Risk of burning fuel falling out	Pass		
	Fuel type	Wood logs		
	Emissions at nominal (nom) / part load (part) heat output (at 13% O²)	nominal	part load	
	Carbon monoxide emission	CO	735	NPD mg/m ³
	Nitrogen oxides emission	Nox	104	NPD mg/m ³
	Emission of organic gaseous carbon	OGC	72	NPD mg/m ³
	Particulate matter emissions	Dust	36	NPD mg/m ³
	Information according to to Regulation (EU) n.305/2011	Registration by the manufacturer		
	Safety and accessibility in use			
	Data for installation to a chimney at nominal (nom) and part load (part) heat output	nominal	part load	
	Flue gas outlet temperature	T _s	329	NPD °C
	Minimum flue draught	p	12	NPD Pa
	Flue gas mass flow	Φ _{f,g}	7,9	NPD g/s

Data for installation to a chimney regarding fire safety on safety test heat output				
Fire safety of installation to the chimney	Tclass	T400 G		
Energy economy and heat retention				
Appliance's thermal output and energy efficiency at nominal (nom) and part load (part) heat output		nominal	part load	
Heat output	P	8	NPD	kW
Space heat output	P _{SH}	8	NPD	kW
Water heat output, if applicable	P _w	-	NPD	kW
Efficiency	η	77,9	NPD	%
Space heating efficiency				
Seasonal space heating efficiency at nominal heat output	η_s	67,9		%
Energy Efficiency	Index (EEI)		103	
	Class		A	
Consumption of electrical auxiliary energy at nominal heat output	e _{lmax}	/		kW
Consumption of electrical auxiliary energy at part load heat output	e _{lmin}	/		kW
Consumption of electrical auxiliary energy at standby	e _{lsb}	/		kW
Sustainable use of natural resources				
Environmental sustainability	NPD			
<p>8. The performance of the product identified in points 1. and 2. is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.</p> <p>Signed for and on behalf of the manufacturer by:</p> <p>Name: Ivan Stanković</p> <p>Place and date: Nova Pazova, 12.12.2025.</p> <p style="text-align: right;">Signature / Stamp : _____</p>				

